

THE STRONG BRAND



TECHNICAL DATA SHEET

Xenial-PET-Recycling-Packaging-Tape

APPLICATION: PACKAGING TAPE - HOT MELT

Backing		Adhesive	Total Thickness (µm)	Adhesivity on steel (N/cm) (AFERA 5001)	Tensile strength (N/cm) (AFERA 5004)	Elongation at break (%) (AFERA 5004)
Type	Thickness (µm)					
Tolerance						
BOPET	19	Hot Melt	37	5,0	40	110

Xenial-Recycling-Packaging-Tape is produced using a post-consumer recycle BOPET film (at least 85% recycled material)

Stocking time

We recommend to use the product within 6 months from the delivery.

Stocking conditions

The product has to be stocked in a dry environment, at a temperature between 15°C and 25°C. The product must be stored protected from dust, humidity and direct sun exposure. It must be stored horizontally and kept in the original packing.

Use

If the storage temperature has been different from what suggested, bring the tape back to that temperature before application. Before applying the tape, remove any trace of dust or any other dirt on the carton and press the tape down thoroughly for a perfect and time lasting adherence.

Important:

The mentioned data stem from an average analysis carried out on our standard production and may undergo unexpected changes. Therefore they are not binding for our company.



Consulting and distribution

TransPak Group ■ Hotline: +49 (0) 6441 9555 – 0 ■ info@transpak.de ■ www.shop.transpak.de