


Specification

Nominal Voltage	12V	
Nominal Capacity(20HR)	9.0AH	
Dimensions	Length	151±2mm (5.95 inches)
	Width	65±1mm (2.56 inches)
	Container Height	93.5±1mm (3.68 inches)
	Total Height (with Terminal)	99±1mm (3.90 inches)
Approx Weight	Approx 2.45 kg (5.40lbs)	
Terminal	T1 / T2	
Container Material	ABS	
Rated Capacity	9.0 AH/0.450A	(20hr , 1.80V/cell,25°C/77°F)
	8.38 AH/0.838A	(10hr, 1.80V/cell,25°C/77°F)
	7.7 AH/1.54A	(5hr, 1.75V/cell,25°C/77°F)
	6.9 AH/2.30A	(3hr, 1.75V/cell,25°C/77°F)
	5.65 AH/5.65A	(1hr, 1.60V/cell,25°C/77°F)
Max. Discharge Current	135A (5s)	
Internal Resistance	Approx 18mΩ	
Operating Temp.Range	Discharge : -15~50°C (5~122°F)	
	Charge : 0~40°C (32~104°F)	
	Storage : -15~40°C (5~104°F)	
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than 2.7A . Voltage	
	14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage	
	13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	CT series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Applications

- ◆ All purpose
- ◆ Uninterruptable Power Supply (UPS)
- ◆ Electric Power System (EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and security system
- ◆ Electronic apparatus and equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto control system



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	17.2	13.1	10.9	9.42	7.28	5.37	4.52	2.68	2.10	1.70	1.39	1.21	0.972	0.812	0.446
1.80V/cell	23.0	16.8	13.1	11.1	8.60	6.25	5.07	2.92	2.26	1.82	1.49	1.29	1.03	0.838	0.450
1.75V/cell	25.9	18.5	14.4	12.0	8.93	6.48	5.30	3.03	2.30	1.86	1.54	1.32	1.05	0.860	0.454
1.70V/cell	28.6	20.1	15.4	12.6	9.30	6.73	5.47	3.10	2.36	1.91	1.57	1.36	1.06	0.877	0.463
1.65V/cell	31.4	21.7	16.3	13.3	9.80	6.90	5.60	3.16	2.46	1.97	1.61	1.39	1.08	0.895	0.469
1.60V/cell	34.7	23.6	17.5	14.3	10.4	7.20	5.65	3.28	2.53	2.03	1.66	1.42	1.09	0.904	0.471


Constant Power Discharge (Watts) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	31.3	24.4	20.3	17.8	13.9	10.3	8.74	5.20	4.09	3.32	2.72	2.37	1.92	1.61	0.883
1.80V/cell	41.6	30.7	24.2	20.6	16.1	11.9	9.73	5.63	4.37	3.54	2.91	2.53	2.03	1.65	0.890
1.75V/cell	46.0	33.1	26.2	22.0	16.6	12.3	10.1	5.82	4.43	3.60	2.98	2.59	2.05	1.69	0.898
1.70V/cell	49.1	35.4	27.5	23.0	17.2	12.7	10.4	5.95	4.54	3.70	3.05	2.64	2.09	1.73	0.914
1.65V/cell	53.5	37.8	29.0	24.2	18.0	12.9	10.6	6.00	4.72	3.80	3.12	2.69	2.12	1.76	0.924
1.60V/cell	57.6	40.1	30.6	25.5	18.8	13.3	10.6	6.24	4.84	3.91	3.21	2.74	2.13	1.78	0.929


Dimensions

T2 Terminal


Unit: mm [inches]




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics



Sales Office

Sweden

CellTech Energy Systems AB,
Äggelundavägen 2, 175 62 Järfälla, Sweden
TEL: +46 8445 7870
FAX: +46 8445 7878
E-mail: order@celltech.se
www.celltech.se

Finland and Baltic countries

Akkuvoima Oy
Höylälamitie 11A, 00380 Helsinki, Finland
TEL: +358 (0)207 999 640
FAX: +358 (0)207 999 641
E-mail: info@akkuvoima.fi
www.akkuvoima.fi

Denmark

CellTech-Harring A/S
Rugmarken 9B, 3520 Farum, Denmark
TEL: +45 7025 2201
FAX: +45 7025 2202
E-mail: info@celltech-harring.dk
www.celltech.dk